

# DELL™ POWEREDGE T410 SERVER



**Dell's high value, flexible tower server, the PowerEdge™ T410, simplifies operations with enhanced performance in a compact, purposeful design.**

**The PowerEdge T410 features the performance of Intel® Xeon 5500 series processors, the availability of up to 6 hard drives (3.5" or 2.5"), DDR3 memory and an optimum chassis depth of 24" for efficient deployment and operation.**

**The PowerEdge T410 was developed with a purposeful design; energy optimised technology, simplified systems management and advanced virtualization capabilities.**

**Inspired by IT professionals like you, the T410 is built to simplify daily operations and maximise uptime.**



## **PURPOSEFUL DESIGN**

The PowerEdge T410 takes advantage of Dell's outstanding system commonality and reliability. Consistent component layout and purposeful placement of interface ports and power supplies helps enable easy installation and redeployment. With a depth of 24", the PowerEdge T410's chassis is easier to access and designed to reside in a back office, retail or small office setting where small chassis and quiet acoustics matter.

Robust, metal hard drive carriers and organised cabling are designed to improve component access and airflow across the server. The PowerEdge T410 purposeful design provides quiet acoustics and an optional LCD screen positioned on the front by the bezel for ease of monitoring.

## **ENERGY-OPTIMISED TECHNOLOGY**

Energy efficiency is designed at the core system level on the PowerEdge T410. Several energy-tuned technologies and standards-based Energy Smart components help reduce power consumption while increasing performance capacity.

Energy Smart 90%+ efficient power supply units are ideally-sized for system requirements on the PowerEdge. Power Management features include power capping, power inventory and power budgeting to best manage power in your specific environment.

## **SIMPLIFIED SYSTEMS MANAGEMENT**

The next-generation of Dell OpenManage™ suite of management tools is designed to provide efficient operations and standards-based commands designed to integrate with existing systems for effective control.

Dell Management Console (DMC) helps simplify operations and create stability by shrinking infrastructure management to one console. This console delivers a single view and a common data source into the entire infrastructure management. Built on Symantec® Management Platform, it has an easily extensible, modular foundation that can provide basic hardware management or more advanced functions, such as asset and security management. Dell Management Console is designed to help reduce or eliminate manual processes, enabling you to save time and money for more strategic technology usage.

Secure and efficient, the Dell Lifecycle Controller delivers "Instant On" integrated manageability through a single access point. The Unified Server Configurator (USC) interface enables persistent access to the tool because it is embedded and integrated into the system for significant flexibility and capabilities. The Lifecycle Controller is a one-stop shop for deploying operating systems with built-in driver installations, BIOS and firmware update and rollback, hardware configuration, and diagnostics. iDRAC6 enterprise - Dells "lights out" out-of-band management solution include remote control & virtual media.

## MODULAR SERVICES

Dell™ Services streamline the integration of new equipment and technology into your existing IT environment by helping to minimise data centre disruption while maximising productivity. Our services are modular so that you can choose the number and level you need to meet your changing needs without being locked into long-term engagements. Whether you seek to simplify enterprise complexity, reduce power and cooling demands, control your footprint, or tackle service management, Dell can provide a smart, cost-effective solution.

Form Factor	
<b>Processors</b>	Latest Dual-Core or Quad-Core Intel® Xeon® 5500 Series Processors
<b>Processor Sockets</b>	2
<b>Front Side Bus or HyperTransport</b>	Intel® QuickPath Interconnect (QPI)
<b>L2/L3 Cache</b>	4MB and 8MB
<b>Chipset</b>	Intel® 5500 Chipset
<b>Memory</b>	Up to 64GB (8 DIMM slots): 1GB/2GB/4GB/8GB DDR3 800MHz, 1066MHz or 1333MHz
<b>I/O Slots</b>	4 PCIe x 8 (x4 routing), 1 PCIe x 16 (x8 routing)
<b>Drive Controller</b>	Chipset based SATA, SAS 5/E, LSI2032 (for tape only), SAS 5/iR (for tape only)
<b>RAID Controller</b>	Optional PERC 6/i SAS/SATA controller with 256MB cache, PERC 6/E and SAS 6/iR (Adapter)
<b>Drive Bays</b>	6x 3.5" Cabled Hard Drives Or 6x 3.5" Hot-swap Hard Drives Or 6x 2.5" Hot-swap Hard Drives And 2x 5.25" drive bays for DVD-ROM, DVD+/-RW, or TBU
<b>Maximum Internal Storage</b>	Up to 6 TB SATA or Near Line SAS
<b>Hard Drives</b>	3.5" SATA (7.2K rpm) 160GB, 250GB, 500GB, 750GB, 1000GB 3.5" Near Line SAS (7.2K rpm) 500GB, 750GB, 1000GB 3.5" SAS (15K rpm) 146GB, 300GB, 450GB 3.5" SAS (10K rpm) 600GB 2.5" SAS (10K rpm) 73GB, 146GB, 300GB 2.5" SATA SSD 25GB, 50GB
<b>Tape Support</b>	RD1000, DAT-72, LTO2-L, LTO3-060, LTO4-120, External versions also available.
<b>Network Interface Cards</b>	Embedded Dual-port Broadcom® NetXtreme II™ 5716 Gigabit Ethernet
<b>Power Supply</b>	Non-Redundant PSU, 525W (80+) Optional Redundant PSU, 580W (80+ GOLD)
<b>Availability</b>	Quad-pack LED Diagnostic or LCD diagnostic with hot-swap HDD chassis; TPM; optional hot-swap hard drives; optional hot-swap redundant power supply; optional PERC 6/i RAID controller with battery-backed cache; tool-less chassis
<b>Video</b>	Integrated Matrox G200
<b>Remote Management</b>	BMC, IPMI2.0 compliant Optional iDRAC6 Enterprise, iDRAC6 Express
<b>Systems Management</b>	Dell OpenManage including Dell Management Console, Server Administrator, Dell Unified Server Configurator & Dell Lifecycle Controller
<b>Rack Support</b>	Tower only (5U rack via 3rd party tray)
<b>Operating Systems</b>	Microsoft® Windows Server® Microsoft® Windows® Standard Business Server Novell SUSE® Linux® Red Hat® Linux® Enterprise

## SIMPLIFY YOUR SERVERS AT [DELL.IE/PowerEdge](http://DELL.IE/PowerEdge)

Dell Products, c/o Cherrywood Science & Technology Park, Dublin 18. Microsoft, MS and Windows are registered trademarks of Microsoft Corporation. Celeron, Celeron Inside, Centrino, Centrino Logo, Core Inside, Intel, Intel Logo, Intel Core, Intel Inside, Intel Inside Logo, Intel SpeedStep, Intel Viiv, Itanium, Itanium Inside, Pentium, Pentium Inside, Xeon and Xeon Inside are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Other trademarks or trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. Pictures are for illustration only. Colour and design details may vary.

